## **Model Information**



## Features

- Metal case
- DIN-Rail mountable
- RS422/485 DB9 male port
- Terminal block
- Optical isolated
- Speed up to 921.6kbps
- no external power supply

Quick Link: | Features | Overview | Hardware Specifications | Ordering Information | Download |

## Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports. The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

## Hardware Specifications

Ports	One RS422/485 port, optical isolated
Speed	up to 921.6kbps
RS422/485 signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
Power	USB bus powered, no external power supply
Driver	Windows 98, ME, 2000, XP, 2003 Server Linux (Kernel 2.4 and up built-in)
Connectors	one DB9 male and terminal block
Dimensions	57×72×22 mm³ (W×L×H) 82×77×22 mm³ with DB9 connector and ears

>Back to top

Ordering Information		
Art.No	639	
Product Name	VScom USB-COMi SI-M	
Packing list	VScom USB-COMi SI-M Adapter USB cable 0,9m CD, English Documentation	
		>Back to top